

MATERIAL SAFETY DATA SHEET
MAGNALUBE-GPTFE/PETROLEUM GREASE

MANUFACTURER:

SAUNDERS ENTERPRISES, INC.
11-51 44TH ROAD
LONG ISLAND CITY, N.Y. 11101

EMERGENCY HEALTH INFORMATION:

EMERGENCY SPILL INFORMATION:

OTHER PRODUCT SAFETY INFO: (718) 729-1000
(718) 729-2628
(718) 729-2671

COMPOSITION/INFORMATION ON INGREDIENTS (CAS NUMBER & PERCENTAGE):

LUBRICATING BASE OIL
SEVERELY REFINED PETROLEUM DISTILLATE
ACGIH-TLV-5MG/M CUBEDIOMG/M3 (MIST) ACGIH STEL

* SEE BELOW 78%
ORGANIC POLYUREA THICKENER
(TSCA PROPRIETY COMPOUND EPA FILE #26847 NON-HAZARDOUS) 22% PTFE

#9002-84-0

*THE BASE OIL MAY BE A MIXTURE OF ANY OF THE FOLLOWING:
CAS 64741884, CAS 6471895, CAS 6471964, CAS 64741975, CAS 64742014, CAS 64742525,
CAS 64742536, CAS 64742547, CAS 64742627, CAS 64742650, OR CAS 72623837.

COMPOSITION COMMENT: ALL THE COMPONENTS OF THIS MATERIAL ARE ON THE TOXIC SUBSTANCES
CONTROL ACT CHEMICAL SUBSTANCES INVENTORY.

THIS PRODUCT FITS THE ACGIH DEFINITION FOR MINERAL OIL MIST.
THE ACGIH TLV IS 5 MG/M3, THE OSHA PEL IS 5 MG/M3.

HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

EYE	NOT EXPECTED TO CAUSE PROLONGED OR SIGNIFICANT EYE IRRITATION.
SKIN	CONTACT WITH THE SKIN IS NOT EXPECTED TO CAUSE PROLONGED OR SIGNIFICANT IRRITATION. SKIN CONTACT MAY CAUSE DRYING OR DEFATTING OF THE SKIN. NOT EXPECTED TO BE HARMFUL TO INTERNAL ORGANS IF ABSORBED THROUGH THE SKIN.
HIGH-PRESSURE EQUIPMENT INFORMATION	ACCIDENTAL HIGH-VELOCITY INJECTION UNDER THE SKIN OF MATERIALS OF THIS TYPE MAY RESULT IN SERIOUS INJURY. SEEK MEDICAL ATTENTION AT ONCE SHOULD AN ACCIDENT LIKE THIS OCCUR. THE INITIAL WOUND AT THE INJECTION SITE MAY NOT APPEAR TO BE SERIOUS AT FIRST; BUT, IF LEFT UNTREATED, COULD RESULT IN DISFIGUREMENT OR AMPUTATION OF THE AFFECTED PART.
INGESTION	IF SWALLOWED, THIS SUBSTANCE IS CONSIDERED PRACTICALLY NON-TOXIC TO INTERNAL ORGANS.
INHALATION	NOT EXPECTED TO BE HARMFUL IF INHALED. CONTAINS A PETROLEUM-BASED MINERAL PROLONGED OR REPEATED INHALATION OF OIL MIST AT AIRBORNE LEVELS ABOVE THE RECOMMENDED MINERAL OIL MIST EXPOSURE LIMIT.
SIGNS AND SYMPTOMS OF EXPOSURE	SKIN DEFATTING: MAY INCLUDE DRYING AND REDDENING OF THE SKIN.

FIRST AID MEASURES:

EYE	NO SPECIFIC FIRST AID MEASURES ARE REQUIRED BECAUSE THIS MATERIAL IS NOT EXPECTED TO CAUSE EYE IRRITATION. AS A PRECAUTION REMOVE CONTACT LENSES, IF WORN, AND FLUSH EYES WITH WATER.
SKIN	REMOVE CONTAMINATED CLOTHING AND SHOES. USE A WATERLESS HAND CLEANER, MINERAL OIL, OR PETROLEUM JELLY TO REMOVE THE MATERIAL THEN WASH SKIN WITH SOAP AND WATER. WASH OR CLEAN CONTAMINATED CLOTHING AND SHOES BEFORE REUSE.
INGESTION	NO SPECIFIC FIRST AID MEASURES ARE REQUIRED BECAUSE THIS MATERIAL IS NOT EXPECTED TO BE HARMFUL IF SWALLOWED. DO NOT INDUCE VOMITING. AS A PRECAUTION, GIVE THE PERSON A GLASS OF WATER OR MILK TO DRINK AND GET MEDICAL ADVICE. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION	IF EXPOSED TO EXCESSIVE LEVELS OF MATERIAL IN THE AIR, MOVE THE EXPOSED PERSON TO FRESH AIR. GET MEDICAL ATTENTION IF COUGHING OR RESPIRATORY DISCOMFORT OCCURS.

NOTE TO PHYSICIANS:

IN AN ACCIDENT INVOLVING HIGH-PRESSURE EQUIPMENT, THIS PRODUCT MAY BE INJECTED UNDER THE SKIN. SUCH AN ACCIDENT MAY RESULT IN A SMALL SOMETIMES BLOODLESS, PUNCTURE WOUND. HOWEVER, BECAUSE OF ITS DRIVING FORCE, MATERIAL INJECTED INTO A FINGER TIP CAN BE DEPOSITED INTO THE PALM OF THE HAND. WITHIN 24 HOURS, THERE IS USUALLY A GREAT DEAL OF SWELLING, DISCOLORATION AND INTENSE THROBBING PAIN. IMMEDIATE TREATMENT AT A SURGICAL EMERGENCY CENTER IS RECOMMENDED.

FIRE FIGHTING MEASURES:

FIRE CLASSIFICATION		CLASSIFICATION (29 CFR 1910.1200): NOT CLASSIFIED BY OSHA AS FLAMMABLE OR COMBUSTIBLE.
FLAMMABLE PROPERTIES	FLASH POINT	(CCC) -525F (-273C)
	AUTOIGNITION	NDA
	FLAMMABILITY LIMITS (% BY VOLUME IN AIR)	LOWER. NA UPPER: NA
	EXTINGUISHING MEDIA	C02, DRY CHEMICAL, FOAM ANI) WATER FOG
NFPA RATINGS		HEALTH 1, FLAMMABILITY 1, REACTIVITY 0
FIRE FIGHTING INSTRUCTIONS		THIS MATERIAL WILL BURN ALTHOUGH IT IS NOT EASILY IGNITED.
COMBUSTION PRODUCTS		NORMAL COMBUSTION FORMS CARBON DIOXIDE, WATER VAPOR AND MAY PRODUCE OXIDES OF SULFUR, NITROGEN AND PHOSPHORUS. COMBUSTION MAY FORM OXIDES OF CALCIUM AND H2S. INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

ACCIDENTAL RELEASE MEASURES:

CLEAN UP SPILLS IMMEDIATELY, OBSERVING PRECAUTIONS IN EXPOSURE CONTROLS/ PERSONAL PROTECTION SECTION.

HANDLING AND STORAGE:

HANDLING & STORAGE: NO SPECIAL REQUIREMENTS.
EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

CONSIDER THE POTENTIAL HAZARDS OF THIS MATERIAL (SEE HAZARDS IDENTIFICATION) APPLICABLE EXPOSURE LIMITS, JOB ACTIVITIES, AND OTHER SUBSTANCES IN THE WORK PLACE WHEN DESIGNING ENGINEERING CONTROLS AND SELECTING PERSONAL PROTECTIVE EQUIPMENT. IF ENGINEERING CONTROLS OR WORK PRACTICES ARE NOT ADEQUATE TO PREVENT EXPOSURE TO HARMFUL LEVELS OF THIS MATERIAL, THE PERSONAL PROTECTIVE EQUIPMENT LISTED BELOW IS RECOMMENDED. THE USER SHOULD READ AND UNDERSTAND ALL INSTRUCTIONS AND LIMITATIONS SUPPLIED WITH THE EQUIPMENT SINCE PROTECTION IS USUALLY PROVIDED FOR A LIMITED TIME OR UNDER CERTAIN CIRCUMSTANCES.

ENGINEERING CONTROLS:

USE IN A WELL-VENTILATED AREA. IF USER OPERATIONS GENERATE AN OIL MIST, USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTIIATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW THE RECOMMENDED MINERAL OIL MIST EXPOSURE LIMITS.

PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION	NO SPECIAL EYE PROTECTION IS NORMALLY REQUIRED.
SKIN PROTECTION	WEAR PROTECTIVE CLOTHING IF ENGINEERING CONTROLS OR WORK PRACTICES ARE NOT ADEQUATE TO PREVENT SKIN CONTACT. SELECTION OF PROTECTIVE CLOTHING MAY INCLUDE GLOVES, APRON, BOOTS, AND COMPLETE FACIAL PROTECTION DEPENDING ON OPERATIONS CONDUCTED. SUGGESTED MATERIALS FOR PROTECTIVE GLOVES INCLUDE: (NITRILE) (VITON) (SILVER SHIELD).
RESPIRATORY PROTECTION	NO RESPIRATORY PROTECTION IS NORMALLY REQUIRED. IF USER OPERATIONS GENERATE AN OIL MIST, DETERMINE IF AIRBORNE CONCENTRATIONS ARE BELOW THE RECOMMENDED MINERAL OIL MIST EXPOSURE LIMITS. IF NOT WEAR A NIOSH APPROVED RESPIRATOR THAT PROVIDES ADEQUATE PROTECTION FROM MEASURED CONCENTRATIONS OF THIS MATERIAL. USE THE FOLLOWING ELEMENTS FOR AIR-PURIFYING RESPIRATORS: PARTICULATE

PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL DESCRIPTION	GREEN GREASE
P/H	NDA
VAPOR PRESSURE	NDA
VAPOR DENSITY	(AIR = 1)
BOILING POINT	NDA
FREEZING POINT	NDA
MELTING POINT	NDA
SOLUBILITY	SOLUBLE IN HYDROCARBON SOLVENTS; INSOLUBLE IN WATER.
SPECIFIC GRAVITY	1.02 @ 15.5/15.6e
EVAPORATION RATE	NA
VISCOSITY	-100 SUS @ 100F
PERCENT VOLATILE (VOL)	NA

STABILITY AND REACTIVITY:

HAZARDOUS DISCOMPOSITION PRODUCTS	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE
CONDITIONS TO AVOID	NO DATA AVAILABLE
INCOMPATIBILITY WITH OTHER MATERIALS	MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS CHLORATES, PEROXIDES, ETC.
HAZARDOUS POLYMERIZATION	POLYMERIZATION WILL NOT OCCUR

TOXICOLOGICAL INFORMATION:

EYE EFFECTS	THE EYE IRRITATION HAZARD IS BASED ON DATA FOR A SIMILAR MATERIAL.
SKIN EFFECTS	THE SKIN IRRITATION HAZARD IS BASED ON DATA FOR A SIMILAR MATERIAL
ACUTE INHALATION EFFECTS	THE ACUTE RESPIRATORY TOXICITY IS BASED ON DATA FOR A SIMILAR MATERIAL
ADDITIONAL TOXICOLOGY INFORMATION	THIS PRODUCT CONTAINS PETROLEUM BASE OILS WHICH MAY BE REFINED BY VARIOUS PROCESSES INCLUDING SEVERE SOLVENT EXTRACTION, SEVERE HYDROCRACKING, OR SEVERE HYDROTREATING. NONE OF THE OILS REQUIRES A CANCER WARNING UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910,1200). THESE OILS HAVE NOT BEEN LISTED IN THE NATIONAL TOXICOLOGY PROGRAM (NTP) ANNUAL REPORT NOR HAVE THEY BEEN CLASSIFIED BY THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) AS; CARCINOGENIC TO HUMANS (GROUP 1). PROBABLY CARCINOGENIC TO HUMANS (GROUP 2A), OR POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B)

ECOLOGICAL INFORMATION:

ECOTOXICITY	NO DATA AVAILABLE
ENVIRONMENTAL FATE	THIS MATERIAL IS NOT EXPECTED TO BE READILY BIODEGRADABLE

DISPOSAL CONSIDERATIONS:

OIL COLLECTION SERVICES ARE AVAILABLE FOR USED OIL RECYCLING OR DISPOSAL. PLACE CONTAMINATED MATERIALS IN CONTAINERS AND DISPOSE OF IN A MANNER CONSISTENT WITH APPLICABLE REGULATIONS. CONTACT YOUR LOCAL ENVIRONMENTAL OR HEALTH AUTHORITIES FOR APPROVED DISPOSAL OR RECYCLING METHODS.

TRANSPORT INFORMATION:

THE DESCRIPTION SHOWN MAY NOT APPLY TO ALL SHIPPING SITUATIONS. CONSULT 49CFR, OR APPROPRIATE DANGEROUS GOODS REGULATIONS, FOR ADDITIONAL DESCRIPTION REQUIREMENTS (E.G. TECHNICAL NAME AND MODE-SPECIFIC OR QUALITY-SPECIFIC SHIPPING REQUIREMENTS).

DOT SHIPPING NAME	NONE
DOT HAZARD CLASS	NONE
DOT IDENTIFICATION #	NONE
DOT PACKING GROUP	NONE
ADDITIONAL INFO	PETROLEUM LUBRICATING GREASE - NOT HAZARDOUS BY US DOT. ADR/RID HAZARD CLASS - NOT APPLICABLE

REGULATORY INFORMATION

SARA 311 CATEGORIES:

- | | |
|---------------------------------------|----|
| 1. IMMEDIATE (ACUTE) HEALTH EFFECTS: | NO |
| 2. DELAYED (CHRONIC) HEALTH EFFECTS: | NO |
| 3. FIRE HAZARD: | NO |
| 4. SUDDEN RELEASE OF PRESSURE HAZARD: | NO |
| 5. REACTIVIW HAZARI): | NO |

FOOD CONTACT STATUS

USDA: U-2 STATUS: THIS PRODUCT IS ACCEPTABLE TO THE USDA FOR USE AS A LUBRICATE IN OFFICIAL MEAT AND POULTRY ESTABLISHMENTS PROVIDED THERE IS NO POSSIBILITY OF THE LUBRICANT OR LUBRICATED PART CONTACTING EDIBLE PRODUCTS.

OTHER INFORMATION

NFPA RATINGS: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0,
HMIS RATINGS: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0,
WHERE (0-LEAST, 1-SLIGHT, 2-MODERATE, 3-HIGH, 4-EXTREME,

PPE: PERSONAL PROTECTION EQUIPMENT INDEX RECOMMENDATION – CHRONIC EFFECT INDICATOR). THESE VALUES ARE OBTAINED USING THE GUIDELINES OR PUBLISHED EVALUATIONS PREPARED BY THE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) OR THE NATIONAL PAINT AND COATING ASSOCIATION (FOR HWIS RATINGS).

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT.

TLV: THRESHOLD LIMIT VALUE	C: CEILING LIMIT
TWA: TIME WEIGHTED AVERAGE	CAS: CHEMICAL ABSTRACT SERVICE NUMBER
STEL: SHORT-TERM EXPOSURE LIMIT	AI-5: APPENDIX A CATEGORIES 0 - CHANGE HAS BEEN PROPOSED
TPQ: THRESHOLD PLANNING QUANTITY	NDA: NO DATA AVAILABLE
RQ: REPORTABLE QUANTITY	NA: NOT APPLICABLE
PEL: PERMISSIBLE EXPOSURE LIMIT	

ISSUED: MARCH 01, 2003

SUPERSEDES: AUGUST 16, 2000

THE ABOVE INFORMATION IS BASED ON THE DATA OF WHICH WE ARE AWARE: AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. SINCE THIS INFORMATION MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR AND SINCE DATA MADE AVAILABLE SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATION OF THE INFORMATION, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF ITS USE. THIS INFORMATION IS FURNISHED UPON CONDITIONS THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE

©Copyright 1999, 2000 Saunders Enterprises, Inc.
Magnalube®-G is a registered Trademark of Saunders Enterprises, Inc.
TEFLON® is a registered Trademark of the DuPont Company. All Rights Reserved.