



MEA-100B

AC Resistance Power Supply

High performance welding power supply for precision welding of small parts

- Intuitive user interface for easy operation
- Compact, desktop footprint
- CE certified units available

KEY FEATURES

- **Secondary constant current control (multi-cycle welding)** – Secondary current feedback every half cycle ensures stable current flow.
- **Single-cycle welding.** First half and second half waves may be programmed separately for small parts welding.
- **Half-cycle welding** – Added precision with half cycle welding capability.
- **Power supply voltage fluctuation compensation control** – Compensates current every half cycle in accordance with fluctuation of power supply voltage.
- **Built-in weld monitor.** Upper and lower limits can be set to monitor the weld quality

	Multi-cycle welding	Single-cycle welding	Half-cycle welding
Secondary constant current control	•	—	—
Power supply voltage fluctuation compensation control	•	•	•

TECHNICAL SPECIFICATIONS

Model	MEA-100B	
Power requirements	Single phase, 200 / 220 / 230 / 240 / 380 / 400 / 460 / 480 VAC +13% -20%, 50/60 Hz, auto-switch (voltage is selectable but factory-fixed on shipment)	
Maximum output capacity	60 kVA (Duty cycle 1.3% when 200 VAC is input) / 66 kVA (Duty cycle 1.3% when 220 VAC is input) / 68 kVA (Duty cycle 2% when 380 VAC is input) / 72 kVA (Duty cycle 2% when 400 VAC is input) / 86 kVA (Duty cycle 2% when 480 VAC is input)	
Control method	Secondary constant-current control / Power supply voltage fluctuation compensation control	
Welding current supply system	Multi-cycle welding / Single-cycle welding / Half-cycle welding	
Control speed	Half cycle	
Welding current accuracy	Secondary constant-current control	Within +/- 2% against +/- 10% fluctuation of power supply voltage, Within +/- 2% against +/- 10% fluctuation of load
	Power supply voltage fluctuation compensation control	Within +/- 3% against +/- 10% fluctuation of power supply voltage
Timer setting (31 schedules)	Multi-cycle welding	SQUEEZE, WELD1, COOL, WELD2, HOLD: 0 – 99 cycle UPSLOPE1, UPSLOPE2, DOWNSLOPE: 0 – 9 cycle PULSATION: 1 – 9 times
	Single-cycle welding	SQUEEZE, HOLD: 0 – 99 cycle first half and second half wave: 0.5 cycle
	Half-cycle welding	SQUEEZE, HOLD: 0 – 99 cycle, half wave: 0.5 cycle
Current setting (31 schedules)	Secondary constant-current control	Current 1, Current 2: 0.20 – 9.99 kA (0.01 kA incremental)
	Power supply voltage fluctuation compensation control	Current 1, Current 2: 10.0 – 99.9% (0.1% incremental)
Current monitoring (31 schedules)	Secondary constant-current control	Upper limit: +1 to +49%, Lower limit: -1 to -49%
	Power supply voltage fluctuation compensation control	Upper limit: 0.01 – 9.99 kA (0.01 kA incremental) Lower limit: 0.01 – 9.99 kA (0.01 kA incremental)
Optional	MB-400K Toroidal coil (required at secondary constant current control)	
External communication	RS-485, bi-directional communication	
Operating environment	Temperature: 0°–45°C, humidity: 90% or less (no condensation), altitude: 1000 meters or lower	
Power consumption	15 W or less in standby	

WEIGHT & DIMENSIONS – CONTROLLER

Dimensions (W x D x H)	5.6 in x 16.4 in x 10.6 in (142 mm x 418 mm x 269 mm)
Weight	14.3 lb (6.5 kg)

WELDING TRANSFORMER SPECIFICATIONS Following transformers can be used when factory supplied power is 200/220 VAC

Model	MT-510AC	MT-520AC	MT-530A *1	MT-25, MT-25A	X16/230
Rating capacity	1.0 kVA	3.2 kVA	6.0 kVA [4.2 kVA]	11.1 kVA	6.4 kVA
Primary rated voltage	200 VAC ±10% 50 / 60 Hz				230
Non-load secondary voltage	1.2 V / 1.8 V / 2.5 V / 3.5 V	2.5 V / 3.2 V / 4.0 V / 5.0 V	2.7 V [2.2 V] / 3.4 V [2.8 V] / 4.3 V [3.6 V] / 5.3 V [4.4 V]	Parallel connection 2.6 V / 4.0 V Series connection 5.3 V / 8.0 V	1.4 to 5.6 in 9 steps
Transformer turns ratio	167:1 / 111:1 / 80:1 / 57:1	80:1 / 63:1 / 50:1 / 40:1	74:1 / 59:1 / 47:1 / 38:1	77:1 / 50:1 38:1 / 25:1	164:1 to 41:1 in 9 steps
Standard max. input capacity	5.6 kVA	18.5 kVA	35.0 kVA [24.2 kVA]	64.0 kVA	16 kVA
Maximum welding current	1600 A	3700 A	6600 A [5500 A]	8000 A	6500 A
Duty cycle	1.5 % or less				8%
Cooling	Air cooled			Water cooled (4 liters / min.)	Air cooled
CE	–	–	–	– : MT-25 / X : MT-25A	–
CCC	X	–	X	X	–

WEIGHT & DIMENSIONS – TRANSFORMERS

Dimensions (W x D x H)*2	7.6 in x 11.2 in x 6.9 in (193 mm x 284 mm x 175 mm)	7.2 in x 14 in x 7.75 in (182.5 mm x 358 mm x 197 mm)	9 in x 14.6 in x 9.6 in (228 mm x 370 mm x 244 mm)	MT-25: 7 in x 14.5 in x 9.5 in (180 mm x 370 mm x 240 mm) MT-25A: 7 in x 18.25 in x 8 in (180 mm x 463 mm x 200 mm)	7.5 in x 14 in x 13 in (191 mm x 356 mm x 330 mm)
Weight	44 lb (20 kg)	77.2 lb (35 kg)	114.6 lb (52 kg)	132.3 lb (60 kg)	95 lb (43 kg)

*1 Values at 60 Hz input are indicated in brackets []. *2 Not including projections



USA Headquarters and Western Technical Center

AMADA WELD TECH
1820 S. Myrtle Ave. • Monrovia, CA 91016 US • T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
ISO 9001 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
(Eastern Technical Center)
High Point, North Carolina
T: (941) 544-5762
southsales@amadaweldtech.com

AMADA WELD TECH
(Midwest Technical Center)
Detroit, Michigan
T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH
(Mexico Office)
El Paso, Texas
T: (915) 881-8765
mxsales@amadaweldtech.com

EUROPE
AMADA WELD TECH
GmbH
Munich, Germany
T: +49-89-839403-0
infode@amadaweldtech.eu

ASIA

AMADA CO., LTD.
Isehara, Japan
T: +81-463-96-3268
sales@miyachi.co.jp

AMADA WELD TECH
SHANGHAI CO., LTD.
Shanghai, China
T: +86-21-6448-6000
jvw@amadaweldtech.com.cn

AMADA WELD TECH KOREA CO., LTD.
Seoul, Korea
T: +82-31-8015-6810
amadaskales@amadaweldtech.co.kr
sales2@amadaweldtech.co.kr

AMADA WELD TECH TAIWAN CO., LTD.
Taipei, Taiwan
T: +886-3-328-3511

AMADA (THAILAND) CO., LTD.
Bangkok, Thailand
T: +66-2170-5900
info@amada.co.th

AMADA VIETNAM CO., LTD.
Ha Noi, Vietnam
T: +84-4-6261-4583
thuyet@amada.co.jp

AMADA WELD TECH
INDIA PVT., LTD.
Bangalore, India
T: +91-80-4092-1749
info@amadaweldtech.in

Specifications subject to change without notice. Copyright© 2024 AMADA WELD TECH INC.
The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

follow us on:



09/24