

Monitor:

- Current
- Voltage
- Time



MM-123B WELD CHECKER®

The MM-123B is a multi-functional weld checker in a compact design which enables operators to monitor, maintain and manage key welding variables that result in changes in the weld process. A successor to the MM-123A, MM-123B features improved accuracy and added voltage monitoring.

MM-123B measures current, time, and voltage. Captured weld data can be easily managed via the Ethernet communication.

KEY FEATURES

- **Compatible with all types of resistance welding power supplies:** AC current, DC inverter, AC inverter, Capacitor Discharge, and Transistor.
- **Long measuring times (AC-type power supply)** Capable of measuring up to 3000 ms, and this feature is suitable for both spot welding and fusing.
- **Limit function:** Set upper and lower limits for current, voltage, and time.
- **Automation ready:** Easily integrated into production environment
- **Ethernet communication:** Remote programming and process data collection
- **Improved accuracy – ISO 17657** (with required MB-400P / MB-800P toroidal coil)

ACCESSORIES



Toroidal coil MB-800P
(ISO17657 compliant)



Toroidal coil MB-400P
(ISO17657 compliant)

Optional accessories

- Voltage detection cable: SK-1205023
- Relay cable (current / voltage): SK-1201740

TECHNICAL SPECIFICATIONS

Model	MM-123B	
Measurement Specification		
Current	Range	0.100 ~ 2.000 kA / 1.00 ~ 20.00 kA / 10.0 ~ 200.0 kA
	Items	Peak / RMS* / arithmetic mean RMS
Voltage	Range	0.30 ~ 6.00 V / 1.0 ~ 20.0 V
	Items	Peak / RMS / arithmetic mean RMS
Measurement time	Range	Max. 3 sec (AC) / 2 sec (DC)
		Single phase AC: 0.5 ~ 150 cycle (50 Hz) / 0.5 ~ 180 cycle (60 Hz)
		AC inverter type: 0.5 ~ max. 1500 cycle (depends on welding current frequency)
		DC inverter type: 0 ~ 2000 ms
		Transistor type: 0.50 ~ 25.00 ms (0.02 ms unit)
		Capacitor discharge type: 0.50 ~ 9.99 ms (in short term) / 5.0 ~ 99.9 ms (in long term)
Monitored parameters	Current / Voltage / Time	31 schedules of upper / lower limit
	No current	Available via input connector
Main body Specification		
Display	4 figures digital display (7 segment LED)	
Detection method	Toroidal coil, voltage detection cable	
Power supply	Single-phase 90 to 250 VAC (50/60 Hz) / 24 V DC \pm 10%	
Power consumption	12 W	
External data output	Ethernet (Protocol: TCP / IP)	
Ambient temperature / humidity during operation	Temperature 0 – 45°C / humidity less than 90% (non-condensation)	
Temperature / humidity during transport	Temperature -10 – 55°C / humidity less than 90% (non-condensation)	

*ISO17657 compliant

WEIGHT & DIMENSIONS

Dimensions (L x W x H)	9.76 in x 2.75 in x 7.36 in (248 mm x 70 mm x 187 mm) excluding projections
Weight	4.4 lb (2 kg)



AMADA WELD TECH INC.

USA Headquarters and Western Technical Center

1820 S. Myrtle Ave. • Monrovia, CA 91016 US
T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
ISO 9001 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
(Eastern Technical Center)
High Point, North Carolina
T: (941) 544-5762
southsales@amadaweldtech.com

AMADA WELD TECH
(Midwest Technical Center)
Detroit, Michigan
T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH
(Mexico Office)
El Paso, Texas
T: (915) 881-8765
mxsales@amadaweldtech.com

EUROPE
AMADA WELD TECH
GmbH
Munich, Germany
T: +49-89-839403-0
info@amadaweldtech.eu

ASIA

AMADA WELD TECH CO., LTD.
Isehara, Japan
T: +81-463-96-1111
sales@miyachi.com

AMADA WELD TECH
SHANGHAI CO., LTD.
Shanghai, China
T: +86-21-6448-6000
syli@amadaweldtech.com.cn
zqzhang@amadaweldtech.com.cn

AMADA WELD TECH KOREA CO., LTD.
Seoul, Korea
T: +82-31-8015-6810
sales@amadaweldtech.co.kr

AMADA WELD TECH
TAIWAN CO., LTD.
Taipei, Taiwan
T: +886-2-2585-0161

AMADA (THAILAND) CO., LTD.
Bangkok, Thailand
T: +66-2170-5900
info@amada.co.th

AMADA VIETNAM CO., LTD.
Ha Noi, Vietnam
T: +84-4-6261-4583

AMADA WELD TECH
INDIA PVT., LTD.
Bangalore, India
T: +91-80-4092-1749
info@miyachiindia.com

Specifications subject to change without notice. Copyright© 2023 AMADA WELD TECH INC.
The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.



follow us on: