



PA-HxxxA

Programmable Pulsed Arc Power Supplies


The PA-HxxxA range of programmable pulsed arc power supplies are linear DC precision arc-welding units extensively used in contactless, high-speed, solder free coil and wire termination applications. Available for single output laboratory use or multi output high-speed automation applications, these units employ state-of-the-art closed-loop electronic arc control circuitry to deliver output accuracies and repeatability better than 1% with currents up to 100 A.

Welding currents and profiles are fully programmable with real-time graphical oscilloscope feedback that provides process monitoring and quality assurance Pass/Fail criteria as standard.


KEY FEATURES

- Easy to use, intuitive color touch screen with graphical weld tracing
- Constant current arc control to within 1% accuracy
- Single or dual pulse outputs
- Single phase, 115 VAC or 230 VAC operation
- Isolated RS-232 port for PC or PLC programming
- 99 memory locations for either single or double pulse weld profiles
- Weld limits for voltage and current provide instant feedback on weld process
- Built-in weld counter
- Fully programmable, upslope, peak and downslope

TYPICAL APPLICATIONS




Connector pin termination



Micro wire pin connections



TIG ball & wire combination



Coil termination

TECHNICAL SPECIFICATIONS

Model	PA-H020A	PA-H040A	PA-H060A	PA-H100A
Maximum output current	20 Amps DC	40 Amps DC	60 Amps DC	100 Amps DC
Minimum current	2 Amps DC	4 Amps DC	6 Amps DC	10 Amps DC
Duty cycle	5% @ 20 A	5% @ 40 A	5% @ 60 A	5% @ 100 A
Open circuit voltage	80 VDC	60 VDC	60 VDC	45 VDC
Options	1, 2 or 4 outputs	1 or 2 outputs	1 output Multi output on request	1 output Multi output on request
Mains supply 50/60Hz	110 V/230 VAC +/-15%	110 V/230 VAC +/-15%	110 V/230 VAC +/-15%	380/415/460 VAC 3 phase
Up slope time (0.1 ms steps)	0.1 - 99.9 ms	0.1 - 99.9 ms	0.1 - 99.9 ms	0.1 - 99.9 ms
Peak weld time (0.1 ms steps)	0.1 - 999.9 ms	0.1 - 999.9 ms	0.1 - 999.9 ms	0.1 - 999.9 ms
Down slope time (0.1 ms steps)	0.1 - 999.9 ms	0.1 - 999.9 ms	0.1 - 999.9 ms	0.1 - 999.9 ms
2nd pulse weld delay time	1 - 999 ms	1 - 999 ms	1 - 999 ms	1 - 999 ms
Cooling (overheat protected)	Fan	Fan	Fan	Fan
Max gas pressure	1 bar - single output	1 bar - single output	1 bar - single output	1 bar - single output
Gas pre/purge timing	Programmable	Programmable	Programmable	Programmable
Weld schedules	99 for either single or double pulse weld profiles			

WEIGHT & DIMENSIONS

Model	PA-H020A	PA-H040A	PA-H060A	PA-H100A
Dimensions (W x D x H)	10.6 in x 19.3 in x 11.8 in (270 mm x 490 mm x 300 mm)	10.6 in x 19.3 in x 11.8 in (270 mm x 490 mm x 300 mm)	10.6 in x 19.3 in x 11.8 in (270 mm x 490 mm x 300 mm)	22 in x 17.5 in x 8.7 in (560 mm x 445 mm x 220 mm)
Weight	84 lb (38 kg)	84 lb (38 kg)	84 lb (38 kg)	92.6 lb (42 kg)



USA Headquarters and Western Technical Center

AMADA WELD TECH
1820 S. Myrtle Ave. • Monrovia, CA 91016 US • T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
ISO 9001 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
(Eastern Technical Center)
High Point, North Carolina
T: (941) 544-5762
southsales@amadaweldtech.com

AMADA WELD TECH
(Midwest Technical Center)
Detroit, Michigan
T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH
(Mexico Office)
El Paso, Texas
T: (915) 881-8765
mxsales@amadaweldtech.com

EUROPE
AMADA WELD TECH
GmbH
Munich, Germany
T: +49-89-839403-0
infode@amadaweldtech.eu

ASIA

AMADA CO., LTD.
Isehara, Japan
T: +81-463-96-3268
sales@miyachi.co.jp

AMADA WELD TECH
SHANGHAI CO., LTD.
Shanghai, China
T: +86-21-6448-6000
jwu@amadaweldtech.com.cn

AMADA WELD TECH KOREA CO., LTD.
Seoul, Korea
T: +82-31-8015-6810
amadadasales@amadaweldtech.co.kr
sales2@amadaweldtech.co.kr

AMADA WELD TECH TAIWAN CO., LTD.
Taipei, Taiwan
T: +886-3-328-3511

AMADA (THAILAND) CO., LTD.
Bangkok, Thailand
T: +66-2170-5900
info@amada.co.th

AMADA VIETNAM CO., LTD.
Ha Noi, Vietnam
T: +84-4-6261-4583
thuyet@amada.co.jp

AMADA WELD TECH
INDIA PVT., LTD.
Bangalore, India
T: +91-80-4092-1749
info@amadaweldtech.in

Specifications subject to change without notice. Copyright© 2024 AMADA WELD TECH INC.
The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

follow us on:

