



Pulsed Nd:YAG Air Cooled Laser Welders

ML-2051A / ML-2050A / ML-2150A

Our pulsed Nd:YAG lasers are designed to meet the stringent demands of precision welding applications including medical devices, photonic devices, and small or delicate components. They are the result of a multi-year development effort, which leveraged AMADA WELD TECH's hands-on experience supporting the industry's foremost manufacturers.

These state-of-the-art lasers are air cooled, provide exceptional pulse energy and branch balance stability, and feature real-time power feedback, 20-segment pulse shaping, and up to three time-shared or three energy-shared fiber outputs.


KEY FEATURES

- Real time power feedback ensures the pulse-to-pulse energy stability which is essential for successful spot welding and process control
- Exceptional branch balance stability yields tight control over post weld shift in critical welding applications by providing precisely balanced laser pulse energy and weld nugget formation on every shot
- 20 segment pulse shaping permits quick and easy optimization of weld schedules for a variety of materials, produces deep penetration welds with low weld splatter and helps to eliminate cracking in difficult-to-weld materials
- Up to three time-share or energy-share outputs

TYPICAL APPLICATIONS




Auto valve laser application



High speed weld



Laser welding aerospace honeycomb



Small gauge wire welding

TECHNICAL SPECIFICATIONS

Parameter	ML-2051A	ML-2050A	ML-2150A
Maximum average power	5 Watts	15 Watts	25 Watts
Maximum pulse energy	5 J @ 5.0 ms	15 J @ 5.0 ms	25 J @ 5.0 ms
Maximum peak power	2.5 kW	4.0 kW	6.0 kW
Time share outputs	Up to 3		
Energy outputs	Up to 3		
Pulse width (resolution)	0.2 → 10 mS (0.02 mS < 5 mS and 0.1 mS ≥ 5 mS)		
Repetition rate	1 - 30 pps		
Input voltage	200/220/240 VAC +10% / -15%, 50/60 Hz, 1Ø		
Breaker rated current / recommended service	15 A		
Schedule set	32 schedules		
Start delay time Schedule change time	1 mS, 4 mS, 8 mS, 16 mS selectable		
Ambient operational temperature	41 - 86°F (5 - 30°C)		
Alarm for lamp life	Preset number of shots or input power value to lamp		
RS-485: type baud rate parity stop bits	Full duplex or half duplex 9,600 bps, 19,200 bps or 38,400 bps Even, odd, or no parity bit 1 or 2		
Cooling	Air cooled. No external water required.		
Time share shutter speed	≤50 mS		
Dust proof optics	Yes		

WEIGHT & DIMENSIONS

Controller dimensions (W x D x H)	12.2 in x 26.2 in x 27.2 in (310 mm x 665 mm x 700 mm)
Weight	154 lb (70 kg)



USA Headquarters and Western Technical Center

AMADA WELD TECH
 1820 S. Myrtle Ave. • Monrovia, CA 91016 US • T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
 ISO 9001:2015 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
 (Eastern Technical Center)
 High Point, North Carolina
 T: (941) 544-5762
southsales@amadaweldtech.com

AMADA WELD TECH
 (Midwest Technical Center)
 Detroit, Michigan
 T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH SHANGHAI CO., LTD.
 Shanghai, China
 T: +86-21-6448-6000
jwu@amadaweldtech.com.cn

AMADA WELD TECH KOREA CO., LTD.
 Seoul, Korea
 T: +82-31-8015-6810
sales@amadaweldtech.co.kr
sales2@amadaweldtech.co.kr

AMADA WELD TECH TAIWAN CO., LTD.
 Taipei, Taiwan
 T: +886-3-328-3511

AMADA (THAILAND) CO., LTD.
 Bangkok, Thailand
 T: +66-2170-5900
info@amada.co.th

AMADA VIETNAM CO., LTD.
 Ha Noi, Vietnam
 T: +84-24-6261-4583
thuyet@amada.co.jp

AMADA WELD TECH INDIA PVT., LTD.
 Bangalore, India
 T: +91-80-4092-1749
info@amadaweldtech.in

Specifications subject to change without notice. Copyright© 2026 AMADA WELD TECH INC. The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

follow us on:

