



NH-4000A

Constant Heat ACF Laminating System

AMADA WELD TECH's NH-4000A series ACF Laminating/Pre-Bonding system is designed specifically for connecting displays to PCB using Anisotropic Conductive Adhesive (ACA) and flex foils. The ACF laminating/pre-bonding process is the first step to apply the adhesive material to the part(s).

The NH-4000A systems utilize constant heat technology through the integrated system temperature controller, a pneumatic bond head and customized thermodes.


The NH-4000A product range includes various models with different product handling features such as linear slides and rotary tables. The systems are designed considering ergonomic standards offering maximized production output. All process parameters are embedded into the system, ensuring consistent process quality and operator independence.

The NH-4000A systems enable full automatic process control with manual loading and unloading of parts. Each system can be adapted to suit the customer's technical requirements with optional plug & play modules. All modules are mounted on a robust frame construction. The system offers the best stability supporting applications down to the finest pitch.


KEY FEATURES

- Compact and flexible standard systems for high quality connections
- Ideal price-performance (throughput) ratio
- Robust frame construction
- User friendly system configuration including optional plug & play modules
- Constant heat process control proven technology
- Included in standard system configuration:
 - X-Y Hot Bar Planarity Adjustment
 - Electronic Temperature & System Control
 - Pneumatic Bond Head
 - Digital Bond Force Readout
- CE approved


TYPICAL APPLICATIONS




CCD camera



Multiple flex



Flex-PCB



LCD display

TECHNICAL SPECIFICATIONS

Power requirements	100 - 240 VAC / Single Phase / 50/60 Hz (16 Amps max)
Air supply	6 - 8 bar [87 - 116 psi], clean dry & filtered air
Fixture assembly baseplate dimensions	5.9 in x 5.9 in (150 mm x 150 mm)
Fixture weight	1.0 kg max (per product fixture)
Heat hot bar size (length x width)	Min 0.11 x 0.4 in (3 x 1 mm) / Max 2.95 x 0.19 in (75 mm x 5 mm)
Starting operation	Two hand control
Start-up time	< 5 minutes
Operating temperature	15 - 40° C
Operating humidity	Max 93% @ 40° C
Certification	CE approved

BONDING HEAD & TEMPERATURE CONTROLLER TECHNICAL SPECIFICATIONS

Force range	8 – 80 N @ 6 bar / 60 – 750 N @ 6 bar		
Bond Head stroke (max)	1.77 in (45 mm)		
Bond level height	1.57 in (40 mm)		
Free Z space for components	0.78 in (20 mm)		
Temperature range		Heat	60 to 600° C
Idle	25 to 300° C	Heat extended range	60 to 999° C
Baseheat	25 to 300° C	Postheat	25 to 999° C
Preheat	60 to 500° C		
Time period (in 0.1 sec increments)		Rise to heat time	0 to 9.9 seconds
Base Heat	0 to 99.9 seconds	Heat	0.1 to 99.9 seconds
Rise to Preheat Time	0 to 9.9 seconds	Postheat	0 to 99.9 seconds
Preheat	0 to 99.9 seconds or continuous		

ACF LAMINATING MODULE TECHNICAL SPECIFICATIONS

ACF tape configuration	2-layer
ACF tape width	0.4 - 0.16 in (1 - 4 mm)
ACF tape feeding indexing	Min 0.11 in (3 mm) Max 2.95 in (75 mm)
ACF tape placement accuracy*	X-direction ± 0.5 mm / Y-direction ± 0.2 mm
Total cycle time incl. movement (excl. bond process time)*	Feeding cycle time@ 3 mm: < 4.8 sec Feeding cycle time@ 75 mm: < 8.0 sec
Laminating area (length x width)	Min 0.11 x 0.4 in (3 x 1 mm) / Max 2.95 x 0.16 in (75 x 4 mm)
Peeler mechanism	Pneumatic
ACF tape cutting method	Half-cut
Tape feeding	DC-motor (encoder controlled)
Tension control	Sensor controlled (closed loop)

*Validated at 4 mm ACF tape width, x-direction is tape feeding direction, y-direction is perpendicular

MODEL SPECIFICATIONS

NH-4121A base	No movement
NH-4221A linear slide (manual 2-position front-rear slide)	Stroke between front and bonding position: 7.87 in (200 mm) fixed
NH-4321A rotary table (manual 2-position)	Turntable diameter: 14.96 in (380 mm)
NH-4421A automatic rotary table (pneumatic 2-position)	Turntable diameter: 14.96 in (380 mm) Turntable movement time: < 2 seconds

WEIGHT & DIMENSIONS

Dimensions (W x D x H)	24.21 in x 27.36 in x 25.59 in (615 mm x 695 mm x 650 mm)
Weight	132.27 lb (60 kg)



USA Headquarters and Western Technical Center

AMADA WELD TECH
1820 S. Myrtle Ave. • Monrovia, CA 91016 US • T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
ISO 9001:2015 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
(Eastern Technical Center)
High Point, North Carolina
T: (941) 544-5762
southsales@amadaweldtech.com

AMADA WELD TECH
(Midwest Technical Center)
Detroit, Michigan
T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH
(Mexico Office)
El Paso, Texas
T: (915) 881-8765
mxsales@amadaweldtech.com

EUROPE
AMADA WELD TECH
GmbH
Munich, Germany
T: +49-89-839403-0
info@amadaweldtech.eu

ASIA

AMADA CO., LTD.
Isehara, Japan
T: +81-463-96-1111
amd_microweld_sales@amada.co.jp

AMADA WELD TECH
SHANGHAI CO., LTD.
Shanghai, China
T: +86-21-6448-6000
jvu@amadaweldtech.com.cn

AMADA WELD TECH KOREA CO., LTD.
Seoul, Korea
T: +82-31-8015-6810
amadadasales@amadaweldtech.co.kr
sales2@amadaweldtech.co.kr

AMADA WELD TECH TAIWAN CO., LTD.
Taipei, Taiwan
T: +886-3-328-3511

AMADA (THAILAND) CO., LTD.
Bangkok, Thailand
T: +66-2170-5900
info@amada.co.th

AMADA VIETNAM CO., LTD.
Ha Noi, Vietnam
T: +84-4-6261-4583
thuyet@amada.co.jp

AMADA WELD TECH
INDIA PVT., LTD.
Bangalore, India
T: +91-80-4092-1749
info@amadaweldtech.in

Specifications subject to change without notice. Copyright© 2025 AMADA WELD TECH INC.
The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

follow us on:

